




SPD MOT
MOTOR MANAGEMENT INTERFACE



CONTENTS

This installation manual has been written by the manufacturer and it is considered integrating part of this product.

The information included are intended for the expert technicians who execute the installation and the extraordinary maintenance of the product.

The expert technicians must have specific competences and particular abilities in order to carry out correctly and safely their work.

The constant observance of the information included in this manual guarantees safety of men, energy serving and a longer duration of product operative-life.

In order to avoid wrong handling and the consequent risk of accidents, it is important to read this manual carefully, keeping scrupulously to guidelines according to the supplied information.

DESCRIPTION	PG 4
FEATURES	PG 5
APPLICATIONS	PG 6
TECHNICAL SPECIFICATIONS	PG 7
MODULE DESCRIPTION	PG 8
INSTALLATION	PG 11
WIRING DIAGRAMS	PG 13
PROGRAMMING	PG 17
PROBLEM SOLVING	PG 18
REPAIR AND WARRANTY POLICIES	PG 19

CONFORMITY DECLARATION

All the devices of the YACHTICA® system are designed in order to comply the directives:

- EN 60945 Maritime navigation and radiocommunication equipment and system.
- IEC 61000;

All the devices of the YACHTICA® system are tested and found to comply with the specification of the CE marking.



All brand names, product names and trademarks are property V.Y.C. Srl.

©2020 V.Y.C. Srl

**DESCRIPTION**

The SPD MOT is equipped with an integrated programmable microcontroller used to control a motor, using a couple (up/down) of relay outputs with programmable software protection.

The module allows the control and the management of electrical motors at 12/24VDC/AC 110/220VAC (with a maximum load of 5A for each output), or dry contact devices as control unit for curtains or TV lift.

The module has 4 programmable dry contact inputs that can be used with push-buttons or sensors.

The module can be used in stand-alone mode or connected to other modules of the YACHTICA® system through the use of the BUS system EasyBUS. It can be easily programmed allowing to create global scenes controlled by push-buttons and/or integrated to be controlled by smartphone/tablet or touch screen.

FEATURES**1 Coupled relay outputs**

The module allows to manage a motor powered directly with the module or by a dry contact control unit. The outputs can be used as a couple (up/down), allowing an electrical and/or software interlock. The outputs can be used also to control on/off lighting sources (same power input must be used).

4 Programmable dry contact inputs

The module allows single output control using the 4 dry contact inputs where push-buttons or sensors can be connected. The inputs are programmable using the YACHTICA® software Cabot.

EasyBUS communication

The module is able to communicate with other devices of the YACHTICA® automation system when connected inside an EasyBUS network. The removable EasyBUS connecting block is used to link the module to the other modules of the same EasyBUS network.

Cabot programming software

The module can be programmed, managed and monitored using the YACHTICA® software Cabot.

Stand-alone mode

The module has a standard programming that allows to manage outputs and light presets, connecting push-buttons or sensors to the dry contact inputs.

Detachable terminal block


All the terminal block of YACHTICA® modules are detachable, allowing a simple wiring and a quick replacement without the need to disconnect any cable, with a high level of security and stability of the system.

Tropicalized electronic

All the YACHTICA® modules have a tropicalization treatment in order to prevent a deterioration due to the humidity and sea mist.




APPLICATIONS




TECHNICAL SPECIFICATIONS

SPECIFICATION		DETAILS
Electronic power supply	20-28V _{DC}	
Electronic requirements	0,4W (16mA @24V _{DC} , 32mA @12V _{DC})	
Outputs power supply	Max 230V	
Outputs	2	
Dry contact inputs	4	
Load ratings	resistive load @125-230Vac: 5A; inductive load @125-230Vac: 3A; resistive load @12-24Vdc: 4A; inductive load @12-24Vdc: 2A (a reverse diode on the load must be used).	
Default address	32	
Working temperature	+5°/+50° C (41°/122° F)	
Storage temperature	-40°/+70° C (-40°/+158° F)	
Humidity	15%/90% non condensing	
Heat dissipation (@Ta=40°C, maximum load)	0,85W	
IP Protection	IP20	
Enclosure	Self-extinguishing UL94-V0	
Color	RAL 7053	
Dimensions (LxHxD)	55x44x15 mm (wiring excluded)	
Weight	50g	
Self-extinguishing UL94-V0		CE: EN60945; EN61000-4-2; EN61000-4-3; EN61000-4-4; EN61000-4-5; EN61000-4-6; EN61000-4-11; CISPR 16-1-1;



MODULE DESCRIPTION



#	CONNECTORS, LED, INDICATORS	DESCRIPTION
1		<p>2 poles detachable connector; Maximum cable section: 1,5mm² (12AWG); Electronic power supply connector; +: positive 20-28VDC; C: negative 20-28VDC. Be sure that all the negative poles of all the power supplies used for electronic are in parallel.</p> <p>NOTE: it is necessary to use a dedicated stabilized power supply for the electronic of all the modules inside a switchboard. It's important that modules installed into different switchboards connected together have negative poles in parallel (the use of YACHTICA® AMP 102D is suggested).</p>
2		<p>2 poles detachable connector; Maximum cable section: 1,5mm² (15AWG); EasyBUS connector; A: BUS A pole; B: BUS B pole. Be sure that cabling of BUS connector is consistent for all the modules in the network. This avoid bad working of the system.</p>
3		<p>Inputs path connector; 4 dry contact inputs connector; IN1: orange; IN2: yellow; IN3: green; IN4: blue; C: red common.</p>
4		<p>5 poles connector; Maximum cable section: 2,5mm² (12AWG); Motor connector; NC1: normally close contact (same power source); C1: common contact 1; NO1: normally open contact 1; C2: common contact 2; NO2: normally open contact 2;</p>



#	CONNECTORS, LED, INDICATORS	DESCRIPTION
5		Green LED, PWR. On if electronic power supply is given.
6		Orange LED, BUS. <i>LED Blinking:</i> the module is connected to other modules in an EasyBUS network and is not the master module. Blinking frequency depends on the address of the module; <i>LED On:</i> the module could be the master of an EasyBUS network or could fail to communicate with the rest of the network ⁽¹⁾ .

⁽¹⁾ See PROBLEM SOLVING paragraph

INSTALLATION

Important notes

The following information are intended for the expert technicians who execute the installation and the extraordinary maintenance of the product. The installation and the maintenance of the module must be executed by qualified technicians, respecting the Norm of the installation country.

The expert technicians must have specific competences and particular abilities in order to carry out correctly and safely their work.

The constant observance of the information included in this manual guarantees safety of men, energy serving and a longer duration of product operative-life. Keep this manual and notes included.

In order to avoid wrong handling and the consequent risk of accidents, it is important to read this manual carefully, keeping scrupulously to guidelines according to the supplied information.

Electrical tension may cause shock and severe burns. Be sure to turn off the electrical supply before carrying out any type of work on the connectors. Omission of observation of these safety measures may cause death or severe lesions to people as well as great material damages.

Before proceeding with the use of the modules, make sure that electric installation, carried out by a qualified technician in conformity with the Technical Norms, corresponding to the class of homologation of the electrical system, is provided with the devices prescribed for the protection against direct and indirect contacts and electrical surcharges.

The modules of the YACHTICA® must be exclusively used in connection with other modules and external components which are conformed to the Norms comparative to the product.

Do not use the module if, upon visual inspection, it shows deterioration of the enclosing box or if the screening wraps of the feeding cables show any wear and tear or damage.

The YACHTICA® system may not be used to carry out safety and accident prevention functions since it does not have the redundancy requirements lawfully requested.

The installer must verify the correct installation and operation of the product.
It is prohibited to use the product for improper purposes or purposes different from those provided

V.Y.C. Srl shall not be held liable for any damage of any sort or kind in case of module used or installed incorrectly.

It is prohibited to tamper or to modify the product.



WIRING DIAGRAMS

Before starting

Always switch off the electronic and outputs power supply before carrying out any type of electrical connection on the module.

NOTE: use a dedicated stabilized power supply for electronic modules installed into a switchboard. If into an EasyBUS network more than one power supply is used (for instance, one power supply for each switchboard containing YACHTICA® modules) be sure that all the negative poles of all the power supplies are in parallel (it is suggested to use YACHTICA® AMP 102D).

The module is intended for internal use. Install it in dry place in order to respect the specifications described in the TECHNICAL SPECIFICATIONS paragraph of this manual.

Blackout management

The YACHTICA® modules manage the states of lack of power supply both for the electronic and the power in case of dimming modules.

Lack of electronic power supply (all modules).

In case of lack of this tension the module switch off. After the blackout the outputs come back to their latest values before the blackout.

Lack of power supply for outputs (dimmer modules).

In case of lack of power supply for the outputs, the dimmer modules show this with a blinking of FUSE PROTECTION LED and the lighting icons on the display will disappear. After the blackout, if no problem occurs, the outputs come back to their latest values.

Addressing

Each YACHTICA® module placed into an EasyBUS network must have a unique address. The default address for all YACHTICA® modules is 32 and Max Address 33. Before connect the BUS connectors of more modules in the same net, be sure that they have a different address. It is possible to address the module using the display.

It is possible to change the address of a module using the YACHTICA® programming software Cabot.

NOTE: a module cannot communicate with other modules in the same net if its Address is upper than the Max Address of the others (see Cabot manual).

Shown below different wiring diagrams that can be used when installing a SPD MOT module.

NOTE: the common contact input of the power is unique, so the power input source must be the same for both outputs (i.e. in case a use of the module to drive two light circuits on/off, it is not possible to use a 230Vac for common 1 and 24Vdc for common 2).

NOTE: all the YACHTICA® modules installed in an EasyBUS network must have the negative pole of electronic power supply in parallel. If this specification is not verified unexpected behaviour of the system can happen.

NOTE: it is not possible to wire an EasyBUS network in a ring. If this specification is not verified unexpected behaviour of the system can happen.

For particular wiring ask for YACHTICA® assistance.


WARNING: it is suggested to protect each output with a fuse according to the wiring used. Sizing the protection according to the wires used and to the load connected to them.

CAUTION: verify carefully that the terminal blocks are fully insert in their position and that the wires are fully insert in their position and screwed correctly.


CAUTION: the terminal block are tested and certified for use with flexible or rigid cord. The component builder does not contemplate the use of tips whose use is the responsibility of the installer. In this case it is recommended the utmost attention in the crimping that must be uniform on all 4 sides to avoid the creation of contact tips.



SCHEME 1: Direct wiring for AC motors



SCHEME 2: Direct wiring for DC motors




**SCHEME 3: Direct wiring for dry contact motors****PROGRAMMING****STANDARD PROGRAMMING**

By the use of the 4 dry contact inputs it is possible to control the motor connected. The functionalities of the inputs and outputs can be tested using Cabot.

STANDARD PROGRAMMING

This programming allows the activation of each output by pressing of the inputs, in the following way.





# IN	FUNCTION NAME	DESCRIPTION
(1-2)	Motor 2B with Stop	The press of one of the 2 inputs of each couple closes the corresponding outputs to control the corresponding motor (so open and close) for a time of 30s, with a software interlock that avoid the damage of the motors directly powered from the module. The outputs which control motors will never be closed contemporary. The Stop of the motors is done by a new press on the last input pressed.
(3-4)	Momentary Switch	The press of one of the 2 inputs closes the corresponding outputs to control motor (so open and close) by the time the input is holded. The Stop function depends on the functionality of the motor control unit (verify the control unit instruction manual).

Programming with Cabot

The module can be programmed using the YACHTICA® software Cabot. Read the manual of the software for all the information needed about Cabot and the module programming.

For programming examples surf the link www.yachtica.com

For advanced programming requested contact YACHTICA® technical department if needed.



PROBLEM SOLVING

PROBLEM	POSSIBLE CAUSE	POSSIBLE SOLUTION
Module does not switch on	The module doesn't receive power supply on the electronic power supply connector	Check that dedicated power supply is working properly, providing right output voltage according to the specifications written in this manual.
	Positive and negative cabling poles inverted	Check that dedicated power supply positive and negative poles are connected in the right way.
The module has the BUS LED always on but its address is not the lowest used in the network	The modules has address higher than the MAX ADR of the module with lowest address in the network	Check the MAX ADR value of the module with lowest address in the network. Set the address of the module according to that value.
	Problem on the BUS cable	Check the cabling of all the BUS chains connected to the same loop of the module. Short circuit or inversion on A-B poles can be present.
Nothing happens while pressing a button connected to an input of the module	The input has no functionality programmed	Use Cabot software to check the programming of the module, in particular for the not working input.
	Broken cable problem	Check that while pressing the button the corresponding label on the display is switched on. Check cabling in case it doesn't happen.

REPAIR AND WARRANTY POLICIES

Merchandise returns

No V.Y.C. Srl merchandise may be returned for credit, exchange or service without prior authorization from V.Y.C. Srl. To obtain warranty service for V.Y.C. Srl products, contact V.Y.C. Srl or an authorized dealer. Request for an RMA (Return Merchandise Authorization) and fill it in properly all the fields, before returning the module. Shipments arriving freight collect or without RMA number shall be subject to refusal.

Return freight charges following repair of items under warranty shall be paid by V.Y.C. Srl, shipping by standard ground carrier. In the event repairs are found to be non-warranty, return freight costs shall be paid by the purchaser. V.Y.C. Srl will provide repairing costs in case the merchandise is not under warranty.

V.Y.C. Srl limited warranty

V.Y.C. Srl warrants YACHTICA® products to be free from manufacturing defects in materials and workmanship under normal use for a period of 2 years from the date of purchase. This warranty extends to products purchased directly from V.Y.C. Srl or an authorized YACHTICA® dealer.

V.Y.C. Srl shall not be liable to honor the terms of warranty if the product has been used in any application other than that for which it was intended or if it has been subject to misuse, accidental damage, modification or improper installation procedures.

Furthermore, this warranty does not cover any products that has had the warranty void label altered, defaced or removed.

V.Y.C. Srl shall, at its option, repair or replace any product found defective, without charge for parts or labor. Repaired or replaced equipment and parts supplied under this warranty shall be covered only by the unexpired portion of the warranty.

Except as expressly set forth in this warranty, V.Y.C. Srl makes no other warranties, expressed or implied, nor authorizes any other party to offer any warranty, including any implied warranties of merchantability or fitness for a particular purpose. Any implied warranties that may be imposed by law are limited to the terms of this limited warranty.

This warranty statement supersedes all previous warranties.



www.yachtica.com

V.Y.C. Srl reserve the rights to change the
specification and data herewith without a notice.
© 2020 by V.Y.C. Srl - All Rights Reserved.